



# AS2070: AEROSPACE STRUCTURAL MECHANICS

## Verification of Rule of Mixtures

Presented by:  
Rishabh  
Chitharth  
Saran Raam S  
Harshal J Patil  
Niranjan B  
P Siva Vardhan

## Aim:

Validate the **Rule of Mixtures** for a composite laminate in Longitudinal Direction (E1)

## Apparatus:

- Compression Moulding Machine to cure the laminate.
- Composite stacking station to make the laminate.
- UTM Machine for Sample Testing.
- Cutter: To cut out testing samples from laminate.



Compression Moulding  
Machine




Cutter

## The Rule of Mixtures:

**Volume Fraction**  $v_f = \frac{V_f}{V_c}$ ,  $v_m = \frac{V_m}{V_c}$ ,  $v_v = \frac{V_v}{V_c}$  such that  $v_f + v_m + v_v = 1$   
 Note that composite density  $\rho_c = \rho_f v_f + \rho_m v_m$ .

**Weight Fraction**  $w_f = \frac{\rho_f}{\rho_c} v_f$



$$E_1 = v_f E_f + v_m E_m$$

## Procedure:

- Preparation of Matrix by mixing **epoxy** with a hardener (reaction catalyst)
- Stack the **fiber laminates**, ensuring thorough **impregnation** with the matrix



Dog bone shaped matrix



Stacking the laminates

- Place the laminate in a **compression moulding machine** and cure for 24 hours
- After curing, mark **dimensions** and **cut** samples using the cutter for burnout and UTM tests



Cutting of the laminates



- Prepare 2–3 samples per vf value to ensure experimental accuracy
- The Vf value is obtained by **burning** the square samples and getting the **remaining mass of matrix**



Square samples

- Test samples on the UTM to obtain **maximum stress and calculate stiffness modulus (Ex)** from the slope of the stress-strain curve




Testing the laminates




Delamination


## Plots:




## Plots:




## Plots:




## Plots:



## Plots:




## Plots:



Delamination

## Plots:



**Ef vs vf**

## Results:

**$V_f = 0$**

$E_m$ : 1584.52 Mpa

**$V_f = 0.592$**

$E_{theoretical}$ : 38192 Mpa  
 $E_{experimental}$ : 7543.93 Mpa

**$V_f = 1$**

$E_f$ : 63423 Mpa



## Sources of Error:

- Improper alignment of fibers
- Improper mixing of matrix and fibers
- Fabrication Defects



## Conclusions:

- **Significant deviation** observed between theoretical and experimental Young's modulus values.
- **Improper fabrication techniques** could have introduced defects affecting material performance.
- Possible **delamination** between layers reduced effective load transfer, **impacting modulus**.



## Acknowledgments

- Thanks to Professor Nidish sir for giving us an hands on opportunity to learn about structural mechanics
- Thanks to Teaching Assistant Senthil sir for helping us with this experiment
- Thanks to Professor David sir for giving us permission to use his Lab.
- Thanks to PHD student Sunil sir for helping us in manufacturing of composites
- Thanks to Vasanthi maam for giving us permission to use her lab for UTM testing

# THANK YOU!